

THIS IS A SAMPLE OF QUALITY CERTIFICATE

QUALITY CERTIFICATE

Product: *gel- revitalizant for power steering pumps*

Lot №

Manufacturer: "x -technology" Ltd.

x FRICTION SURFACE MODIFIER

The present standard applies to x ® gel-revitalizant designed to be used in the hydraulic booster of steering wheel.

Parameter name	Standard according to product acceptance standard	Actual data	Acceptance standard for test methods
1. Color	Blue	Meets the standard	
2 Melting point, °C (with intense stirring)	40	55	ISO 6244 (GOST 4255)
3 Density at 65 °C, kg/m ³	880-980	890	ASTM D 941, D 1298, D 1481 (GOST 3900)
4 Dispersion, μm	5	5	ISO 8781 (GOST 6589)
5 Corrosive effect on metals	Meets the standard	Meets the standard	ASTM D 1743 (GOST 9.080)
6 Water content, %	Absent	-	ISO 3733 (GOST 2477)

Acceptance regulations

Gel-revitalizant for hydraulic booster of steering wheel is accepted by lots. A lot is considered to be an amount of gel manufactured in a single technological cycle and accompanied by a single quality document.

Packaging admission ±1%.

Decision: CONFORMS TO TY Y 24.6-25612000-002-2002 SPECIFICATIONS

Research engineer _____ /...../

Date issued: